



- NOTES:**
- ▣ 32 - 4" Ø POLYLOCK PIPE SEALS ON BOTTOM
 - ▣ Concrete Strength: 30 MPa [min.] Air Entrained [5 - 8%]
 - ▣ Wall Thickness: 102mm - 140mm
 - ▣ 4 - 1/2" Threaded Inserts c/w Threaded Plugs
 - ▣ 4 - 4-Ton Sift-Lift Anchors (per Vault)
 - ▣ 4 - Pulling Eyes - Interior Top Section (Utility Anchors)
 - ▣ Reinforcement: 10M Rebar & 4x4x4/4 WWF
 - ▣ Weight: BOTTOM = 1,391 kg [3,066 lbs.]
TOP = 1,391 kg [3,066 lbs.]
LID = 204 kg [450 lbs.] x 3

Please contact our office for additional information and/or design assistance JAN 16/09

Hy-Grade Precast Concrete
2411 First Street Louth
St. Catharines, Ontario, L2R 6P7
Tel: 1-800-229-8568
Fax: 905-684-8560



www.hygradeprecast.com

Hy-Grade Precast Concrete Products, Inc.
PO Box 148
South Byron, New York, USA 14557
Tel: 1-877-897-2730
Fax: 585-548-2731